

MAXAM+ Dimensional Data



* See Dimensional Notes below

Number of Rows	MAXAM+™ Open Dimensions				MAXAM+ Closed	
	30" Spacing	762 mm Spacing	33" Spacing	838 mm Spacing		
2	3'-10"	1168	3'-10"	1168	3'-10"	1168
3	6'-4"	1930	6'-7"	2007	3'-11"	1207
4	8'-10"	2692	9'-4"	2845	3'-11"	1207
5	11'-4"	3454	12'-1"	3683	4'-0"	1219
6	13'-10"	4216	14'-10"	4521	4'-0"	1219
7	16'-4"	4978	17'-7"	5359	4'-0"	1219
8	18'-10"	5740	20'-4"	6197	4'-1"	1245
9	21'-4"	6502	23'-1"	7036	4'-1"	1245
10	23'-10"	7264	25'-10"	7874	4'-2"	1270
11	26'-4"	8026	28'-7"	8712	4'-2"	1270
12	28'-10"	8788	31'-4"	9550	4'-2"	1270
13	31'-4"	9550	34'-1"	10389	4'-3"	1295
14	33'-10"	10312	36'-10"	11227	4'-3"	1295
15	36'-4"	11074	39'-7"	12065	4'-4"	1321
16	38'-10"	11836	42'-4"	12903	4'-4"	1321
17	41'-4"	12598	45'-1"	13741	4'-4"	1321
18	43'-10"	13360	47'-10"	14580	4'-5"	1346
19	46'-4"	14122	50'-7"	15418	4'-5"	1346
20	48'-10"	14884	53'-4"	16256	4'-6"	1372
21	51'-4"	15646	56'-1"	17094	4'-6"	1372
22	53'-10"	16408	58'-10"	17932	4'-6"	1372
23	56'-4"	17170	61'-7"	18771	4'-7"	1397
24	58'-10"	17932	64'-4"	19609	4'-7"	1397
25	61'-4"	18694	67'-1"	20447	4'-8"	1422
26	63'-10"	19456	69'-10"	21285	4'-8"	1422
27	66'-4"	20218	72'-7"	22123	4'-8"	1422
28	68'-10"	20980	75'-4"	22962	6'-11"	2108
29	71'-4"	21742	78'-1"	23800	6'-11"	2108
30	73'-10"	22504	80'-10"	24638	7'-0"	2134

* See Dimensional Notes below

Number of Rows	MAXAM+ Overall Seat Height					
	9 ⁵ / ₈ " Rise	244 mm Rise	11 ⁵ / ₈ " Rise	295 mm Rise	16" Rise	406 mm Rise
2	2'-2 ⁵ / ₈ "	676	2'-4 ⁵ / ₈ "	727	2'-9"	838
3	3'-0 ¹ / ₄ "	921	3'-4 ¹ / ₄ "	1022	4'-1"	1245
4	3'-9 ⁵ / ₈ "	1222	4'-3 ⁵ / ₈ "	1318	5'-5"	1651
5	4'-7 ¹ / ₂ "	2121	5'-3 ¹ / ₂ "	1613	6'-9"	2057
6	5'-5 ¹ / ₈ "	1654	6'-3 ¹ / ₈ "	1908	8'-1"	2464
7	6'-2 ³ / ₄ "	1899	7'-2 ³ / ₄ "	2203	9'-5"	2870
8	7'-0 ³ / ₄ "	2143	8'-2 ³ / ₄ "	2499	10'-9"	3277
9	7'-10"	2388	9'-2"	2794	12'-1"	3683
10	8'-7 ⁵ / ₈ "	2632	10'-1 ⁵ / ₈ "	3089	13'-5"	4089
11	9'-5 ¹ / ₄ "	2877	11'-1 ¹ / ₄ "	3385	14'-9"	4496
12	10'-2 ¹ / ₂ "	3121	12'-0 ¹ / ₂ "	3680	16'-1"	4902
13	11'-0 ¹ / ₂ "	3366	13'-0 ¹ / ₂ "	3975	17'-5"	5309
14	11'-10 ¹ / ₈ "	3610	14'-0 ¹ / ₈ "	4270	18'-9"	5715
15	12'-7 ³ / ₄ "	3854	14'-11 ³ / ₄ "	4566	20'-1"	6121
16	13'-5 ⁵ / ₈ "	4099	15'-11 ⁵ / ₈ "	4861	21'-5"	6528
17	14'-3"	4343	16'-11"	5156	22'-9"	6934
18	15'-0 ⁵ / ₈ "	4588	17'-10 ⁵ / ₈ "	5451	24'-1"	7341
19	15'-10 ¹ / ₄ "	4832	18'-10 ¹ / ₄ "	5747		
20	16'-7 ¹ / ₂ "	5077	19'-9 ¹ / ₂ "	6042		
21	17'-5 ¹ / ₂ "	5321	20'-9 ¹ / ₂ "	6337		
22	18'-3 ¹ / ₈ "	5566	21'-9 ¹ / ₈ "	6633		
23	19'-0 ³ / ₄ "	5810	22'-8 ³ / ₄ "	6928		
24	19'-10 ³ / ₄ "	6055	23'-8 ³ / ₄ "	7223		
25	20'-8"	6299	24'-8"	7518		
26	21'-5 ⁵ / ₈ "	6544				
27	22'-3 ¹ / ₄ "	6788				
28	23'-0 ⁵ / ₈ "	7033				
29	23'-10 ¹ / ₂ "	7277				
30	24'-8 ¹ / ₈ "	7522				

* DIMENSIONAL NOTES:

- The Open Dimension of bleacher is increased by the depth of front steps when required to access the aisles on front-loaded seating systems.
 - MAXAM Add: 11 ³/₄" (298mm) to Open Dimension w/ CourtSide Seats
 - MAXAM+ Add: 1'-3 ³/₄" (400mm) to Open Dimension w/ CourtSide Seats
 - MAXAM+ Add: 1'-4 ¹/₂" (419mm) to Open Dimension w/ Chairs
- Open and Closed Dimensions are for wall attached application.
 - For Portable Application Add: 2 ¹/₄" (57mm) to Open and Closed Dimensions
 - For Free Standing Application Add: 2 ¹/₄" (57mm) to Open and Closed Dimensions
 - For Reverse Fold Application Add: 2 ¹/₄" (57mm) to Open Dimension
 - For Reverse Fold Application Add: 2 ¹/₄" (57mm) + Row Spacing to Closed Dimension
 - For Recessed Application Add: 6" (157mm) to Closed Dimension for Minimum Recess Depth
- The Open Dimension of bleacher is increased by the depth of front steps when required to access the aisles on front-loaded seating systems.
 - MAXAM Add: 13" (330mm) to Open Dimension
 - MAXAM+ Add: 1'-4¹/₂" (419mm) to Open Dimension
- For Recessed Applications Add: 2 ¹/₄" (64mm) to seat height for minimum recess height.
- The chart above identifies Maximum number of rows for wall attached section lengths 16'-6" (5029mm) or greater.

6. SPECIAL NOTE: For complete dimensional charts referring to smaller sections and other applications including product limitations please reference FASTFACTS or ask your local dealer for details.

MXP™ & Hussey Seatway
MXP and Hussey Seatway are customized to your specifications with the following standard dimensions:

MXP
Row Rise: 4 - 24" (102 - 610 mm)
Row Spacing: 32 - 36" (813 - 914 mm)
Tapered Sections: Up to 22¹/₂ degrees

Seatway™
Row Rise: 10¹/₄" (260 mm), 11" (280 mm),
11⁷/₈" (300 mm), 12⁵/₈" (320 mm)
Row Spacing: 33¹/₂" (850 mm), 35³/₈" (900 mm), 36" (915 mm)